



© 2007. All rights reserved. Black Box Corporation.

FREE 24-hour Tech Support: 724-746-5500
blackbox.com

Rackmountable DB25 Manual Switches



**Rugged, versatile rackmount switches
that are guaranteed for life.**

FEATURES

- Ideal when space is tight and you need to consolidate multiple switches.
- Custom-built to your specifications.
- Pick the switches you need, and we'll install them in the 19-inch Rackmount Chassis that best fits your application!
- Female connectors are standard on each switch.
- Male connectors are available for an additional charge per connector.
- If you order fewer switches than the maximum number the chassis will hold, you can specify additional punchouts for future expansion—free! Just ask Tech Support for your Free Punches Code when you order!
- Choose either a Standard Chassis (SR000A) or a Mini Chassis (SR001A). The maximum number of switches that will fit in either chassis style is indicated in the Tech Specs.
- Guaranteed for life!

OVERVIEW

Rackmount switches are ideal when space is tight and you need to consolidate multiple switches. Each rackmount switch is custom-built to your specifications. Pick the switches you need, and we'll install them in the 19" Rackmount Chassis that best fits your application.

If you order fewer switches than the maximum number the chassis holds, you can specify additional punchouts for future expansion—FREE!

Most switches are available with male or female connectors. For details, call our FREE Tech Support at **724-746-5500**.

First, choose a Standard or Mini Chassis.

Our Standard Rackmount Chassis (SR000A) fits a standard rack. It holds up to eight switch modules, depending on switch size. The Tech Specs ([right](#)) show how many switches of each type you can install in each Rackmount Chassis. To mix switches in a Rackmount Chassis, contact Tech Support.

Our Mini Rackmount Chassis (SR001A) occupies only 3.5 inches (8.9 cm) of vertical space. It generally holds either three ABC or two ABCDE switches.

Then, pick the switches for your application.

Be sure to select switches with connectors that match your cables and equipment, the correct pinning, and the number of switch positions you need. (Remember that an ABC switch has just two positions, not three.)

You can mix several types of switches in the same chassis. If you decide to mix and match, our Tech Support experts can tell you the maximum number of switches you can install in each chassis.

If necessary, specify punchouts.

If there's space left over in your Rackmount Chassis, remember to plan for future expansion by specifying punchouts—extra holes for additional switches. If you want to add switches to the Rackmount Chassis at any time in the future, simply specify the type of switch you'd like a punchout for when you order. There's no extra charge! Our Tech Support experts can provide the FREE Punches Code you'll need to use when ordering.

Need help?

Contact Tech Support—our experts can help you determine the configuration that's best for your application.

TECH SPECS

Number of Switches per Chassis (Maximum)—

Standard (SR000A):

SR025, SR088, SR084, SR015, SR020: 8;

SR026, SR058, SR054: 5;

SR027: 6;

SR059, SR090: 4;

Mini (SR001A):

SR025, SR088, SR084, SR015, SR020, SR027: 3;

SR026, SR058, SR054: 2;

SR059, SR090: 1

Size — Standard: 7"H x 19"W x 5.9"D (17.8 x 48.3 x 15 cm);

Mini: 3.5"H x 19"W x 5.9"D (8.9 x 48.3 x 15 cm)

Item	Code
Rackmount Chassis	
Standard	SR000A
Mini	SR001A
Rackmountable DB25 Manual Switches	
ABC (25 Leads)	
8 per Standard, 3 per Mini	SR025-FFF
8 per Standard, 3 per Mini	SR025-FFF
8 per Standard, 3 per Mini	SR025-MMF
8 per Standard, 3 per Mini	SR025-MMM
ABC (12 Leads)	
8 per Standard, 3 per Mini	SR088-FFF
8 per Standard, 3 per Mini	SR084-FFF
8 per Standard, 3 per Mini	SR015-FFF
8 per Standard, 3 per Mini	SR020-FFF
5 per Standard, 2 per Mini	SR026-FFFFF
5 per Standard, 2 per Mini	SR026-FFMFF
5 per Standard, 2 per Mini	SR026-MMFMM
5 per Standard, 2 per Mini	SR026-MMMMM
5 per Standard, 2 per Mini	SR058-FFFFF
ABCDE (4 Leads)	
5 per Standard, 2 per Mini	SR054-FFFFF
X (25 Leads)	
6 per Standard, 3 per Mini	SR027-FFFF
6-to-1 Parallel	
4 per Standard, 1 per Mini	SR059
6-to-1 Serial	
4 per Standard, 1 per Mini	SR090